



Max. Heat Loss
95 MBH@ $\Delta T=20^{\circ}F$

Max. Heat Loss
95 MBH@ $\Delta T=20^{\circ}F$

Max. Heat Loss
95 MBH@ $\Delta T=20^{\circ}F$

Max. Heat Loss
95 MBH@ $\Delta T=20^{\circ}F$

Max. 38.7 GPM

Thermostatic Radiator Valve

ECM Pumps

AAV

LWCO

AUTO-FEED ASSEMBLY

Expansion Tank

SWIMMING POOL

PENTAIR POOL PUMP

Disclaimer: The Fine Print
 This schematic and notes are illustrative only. It should not be used for any actual installation without engineering or technical advice from trained or licensed professional. No warranty is expressed or implied as to the suitability or workability of this schematic, the pipe sizing and/or the component selection.

CONFIDENTIAL
 THIS DRAWING IS THE PROPERTY OF SOLARNETIX INC.
 AND CAN NOT BE ALTERED, REPRODUCED OR DISTRIBUTED
 WITHOUT WRITTEN PERMISSION

DRAWN	V.T	SCALE	1" NPT (DN25)	SHEET	3 OF 3
	ISSUED		15-07-18		
SIZE	FSCM NO	HI EFFICIENCY COMBI GAS BOILER w. PUMP & DHW 4- HI TEMPERATURE ZONES		DWG NO	REV
					0

